



## Inducoat BV

Postbus 2776  
3800 GJ AMERSFOORT  
The Netherlands  
Chamber of Commerce  
805 94 07 Gooi- en Eemland  
t +31 (0) 33 456 23 94  
f +31 (0) 33 456 25 94  
e info@inducoat.com

Product Data Sheet  
Version 1.0 – September 2008-

### Description

Inducoat Cleaner is a clear water dilutable cleaner based on a quarternary ammonium compound, free of metal compounds and biological degradable.

### Recommended uses

Inducoat Cleaner is used for application on mineral substrates like new and old masonry, plaster and concrete, both external and internal, in order to fight and remove contamination by algae and mould growth and other micro organisms, before finishing these surfaces with an Inducoat product.

### Technical data

Appearance	Colourless liquid
Spec.gravity	1.0 kg/L
Viscosity	Thin liquid
pH	approx. 7
Odour	slight characteristic odour
Flashpoint	Non flammable
Practical consumption	approx. 4-8 m/L, depending on rugosity and porosity of the substrate and the application method

Do not use externally if rain is expected.

Use brushes for water dilutable products.

Rollers: Acrylic of polyester (8 -12 mm).  
For textured surfaces: 14 – 16 mm rollers.

Cleaning of the equipment: water

### Directions for use

To fight and remove algae, mould and other micro-organisms dilute the Inducoat Cleaner as follows:

Cleaner 1 part, water 20 parts (50 ml per liter water)  
Add the Cleaner to the water

In case of very severe mould or algae contamination dilute the Inducoat Cleaner as follows:

Cleaner 1 part, water 9 parts (100 ml per liter water)  
Add the Cleaner to the water.

Apply the diluted Cleaner by roller, brush, spraying at low pressure or sprinkling. Wet the surface sufficiently; the surface should remain wet for at least 5 minutes.

After 24 hours the remains of algae, mould etc should be removed by low pressure water or wet brushing. After drying the surface can be finished with the Inducoat products.

Upon using the Inducoat Cleaner no soap or other synthetic cleaners should be used since otherwise the Inducoat Cleaner becomes ineffective.

Do not use Inducoat Cleaner at temperatures below 5°C.

### Storage stability

At least 1 years from manufacturing date in unopened, original cans. Keep from freezing.

### Safety

Consult the Label text and the Material Safety Data Sheet.

The data herein are given in good faith and based on practical experience and testing. Upon appearance of a new sheet, this version becomes obsolete. No responsibility based on the data given can be assumed, because application and conditions are beyond our control.

